

PATENT COOPERATION TREATY

REC'D 28 JUN 2005

WIPO

PCT

PCT

INTERNATIONAL PRELIMINARY EXAMINATION REPORT (PCT Article 36 and Rule 70)



Applicant's or agent's file reference IME012BWO	FOR FURTHER ACTION See Notification of Transmittal of International Preliminary Examination Report (Form PCT/PEA/416)	
International application No. PCT/IT 03/00510	International filing date (day/month/year) 14.08.2003	Priority date (day/month/year) 14.08.2003
International Patent Classification (IPC) or both national classification and IPC H05B3/34		
Applicant IMETEC S.P.A. et al.		

- This international preliminary examination report has been prepared by this International Preliminary Examining Authority and is transmitted to the applicant according to Article 36.
- This REPORT consists of a total of 5 sheets, including this cover sheet.

☒ This report is also accompanied by ANNEXES, i.e. sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications made before this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions under the PCT).

These annexes consist of a total of 7 sheets.

- This report contains indications relating to the following items:
 - ☒ Basis of the opinion
 - ☐ Priority
 - ☐ Non-establishment of opinion with regard to novelty, inventive step and industrial applicability
 - ☐ Lack of unity of invention
 - ☒ Reasoned statement under Rule 66.2(a)(ii) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement
 - ☐ Certain documents cited
 - ☐ Certain defects in the international application
 - ☐ Certain observations on the international application

Date of submission of the demand 27.07.2004	Date of completion of this report 27.06.2005
Name and mailing address of the international preliminary examining authority:  European Patent Office D-80298 Munich Tel. +49 89 2399 - 0 Tx: 523656 epmu d Fax: +49 89 2399 - 4465	Authorized Officer Gea Haupt, M Telephone No. +49 89 2399-6938 

**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT**

International application No. **PCT/IT 03/00510**

I. Basis of the report

1. With regard to the **elements** of the international application (*Replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report since they do not contain amendments (Rules 70.16 and 70.17)*):

Description, Pages

1, 2, 4, 6-17 as originally filed
3, 5 filed with telefax on 10.03.2005

Claims, Numbers

1-20 filed with telefax on 10.03.2005

Drawings, Sheets

1/2-2/2 as originally filed

2. With regard to the **language**, all the elements marked above were available or furnished to this Authority in the language in which the international application was filed, unless otherwise indicated under this item.

These elements were available or furnished to this Authority in the following language: , which is:

- ☐ the language of a translation furnished for the purposes of the international search (under Rule 23.1(b)).
☐ the language of publication of the international application (under Rule 48.3(b)).
☐ the language of a translation furnished for the purposes of international preliminary examination (under Rule 55.2 and/or 55.3).

3. With regard to any **nucleotide and/or amino acid sequence** disclosed in the international application, the international preliminary examination was carried out on the basis of the sequence listing:

- ☐ contained in the international application in written form.
☐ filed together with the international application in computer readable form.
☐ furnished subsequently to this Authority in written form.
☐ furnished subsequently to this Authority in computer readable form.
☐ The statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.
☐ The statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished.

4. The amendments have resulted in the cancellation of:

- ☐ the description, pages:
☐ the claims, Nos.:
☐ the drawings, sheets:

**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT**

International application No. PCT/IT 03/00510

5. ☐ This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed (Rule 70.2(c)).

(Any replacement sheet containing such amendments must be referred to under item 1 and annexed to this report.)

6. Additional observations, if necessary:

V. Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Statement

Novelty (N)	Yes: Claims	1-20
	No: Claims	
Inventive step (IS)	Yes: Claims	1-20
	No: Claims	
Industrial applicability (IA)	Yes: Claims	1-20
	No: Claims	

2. Citations and explanations

see separate sheet

**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT - SEPARATE SHEET**

International application No. PCT/IT 03/00510

Re Item V

**Reasoned statement with regard to novelty, inventive step or industrial applicability;
citations and explanations supporting such statement**

Reference is made to the following document:

D1: WO 01/24580 A (SUNBEAM PRODUCTS INC) 5 April 2001 (2001-04-05)

The document D1 is regarded as being the closest prior art to the subject-matter of claim 1, and shows (the references in parentheses applying to this document):

A heat blanket comprising an operative unit and a control/power supply unit which can be electrically connected on one side to the power mains and on the other side to the operative unit, wherein:

a) the operative unit comprises:

- a foldable sheet,
- a linear heating element distributed in the sheet

b) the control/power supply unit comprises:

- a power supply group for the heating element
- control means of the power supply for the heating element, wherein the control means comprise:
 - a power supply cut-off means for the heating element,
 - a microprocessor(220), connected to the heating element, to the power supply group and to the cut-off group, set to detect possible anomalies in the power supply conditions of the heating element and to act upon the cut-off group interrupting the power supply of the heating element when said anomalies take place(page 7, lines 6 to 14; figure 1B).

The subject-matter of claim 1 differs from this known heat blanket in that the microprocessor classifies each detected anomaly either as a temporary anomaly or as a definitive anomaly, and in that the interruption of the power supply is reversible in case of a temporary anomaly and irreversible in case of a definitive anomaly.

**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT - SEPARATE SHEET**

International application No. PCT/IT 03/00510

The subject-matter of claim 1 is therefore new (Article 33(2) PCT).

The problem to be solved by the present invention may be regarded as how to design a heating blanket that is safe to use and at the same time allows to continue using it in case of minor safety incidents.

The solution to this problem proposed in claim 1 of the present application is considered as involving an inventive step (Article 33(3) PCT) since the way the microprocessor deals with anomalies in it is neither known, nor rendered obvious by D1 (or any other document part of the prior art). Other documents deal with safety issues but none of them makes this distinction between temporary and definitive anomalies. Additionally, the above-stated technical problem is also not addressed by D1 and none of the control schemes disclosed by D1 would solve this problem.

Claims 2 to 20 are dependent on claim 1 and as such also meet the requirements of the PCT with respect to novelty and inventive step.

10-03-2005

10. MAR. 2005 17:22 PCA +39 02 58301263
IME012BWO

IT0300:

NR. 467 P. 3/16

- 3 -

WO 01/24580 A discloses a remote control system for an electric heat blanket. This system includes a power supply having control means with a circuitry capable of monitoring safety conditions in the blanket and of deactivating the power supply when needed.

US 2001/008236 A1 discloses a safety circuit for an electric heat blanket. This circuit can detect both shorts and breaks and consequently disconnect power when needed.

US-A-5105067 discloses a control system for a heated garment. The system includes a protection circuit that is able to modulate the power supply according to the detected voltage drop.

US 2003/047556 A1 discloses a warming blanket having a safety circuit. The circuit includes means for detecting fault conditions in the blanket by checking the value of the current; when a fault condition is detected, the power is switched off.

The present invention addresses the problem of further improving the safety conditions of a heat blanket.

Consequently, this invention concerns a heat blanket according to claim 1.

The use of a microprocessor allows the variation of the power supply conditions in the heating element to be recognised with the maximum accuracy, and thus ensures rapidity and versatility of intervention in case of anomalies, substantially improving the safety of the

10-03-2005

10. MAR. 2005 17:22

PCA +39 02 58301263

IME012BWO

IT03005

NR. 467 P. 4/16

- 5 -

the blanket;

- number and type of anomalies detected.

According to a characteristic of the invention, each anomaly detected is classified by the microprocessor, either as a temporary anomaly or as a definitive anomaly, whereas the interruption of the power supply of the heating element is reversible in case of temporary anomaly and irreversible in case of definitive anomaly. In this way, an anomaly in any case determines the interruption of the power supply, preventing situations of danger; however, the following behaviour is differentiated according to the type of anomaly detected. Indeed, some anomalies may be due to temporary problems which can be corrected by itself or with a small intervention by the user; this is the case, for example, of overheating (after it has been cooled down the conditions can once again be perfectly safe), or else of interruption of electric conduction in the heating element (this could simply be due to an imperfect electric coupling between the operative and control/power supply units). On the other hand, a situation of short circuit is certainly a source of danger, whatever its cause, and it is thus advisable to exclude the possibility of even just an attempt to switch it back on. A request for a periodical maintenance check may be classified either as a temporary anomaly, or as a definitive anomaly. The first case is preferable if one wishes to leave the user with a certain freedom, whereas the second case is preferable if one wishes to prioritise safety. A block due to a definitive anomaly can be nullified only by an intervention of the authorised assistance service.

Preferably, a temporary anomaly is reclassified by the microprocessor as a definitive anomaly if it reoccurs a predetermined number of times consecutively. The reoccurrence of the same anomaly, indeed, is normally an indication of a permanent structural problem, which thus

- 18 -

CLAIMS

1. Heat blanket comprising an operative unit (20) and a control/power supply unit (40) which can be electrically connected on one side to the power mains and on the other side to the operative unit (20),
5 wherein:
a) the operative unit (20) comprises:
- a foldable sheet (21),
- a linear heating element (22) distributed in
10 the sheet (21), with a first (24) and a second (26) conductor extending one along the other, separated by a first electrically insulating material (25) and enclosed by a second electrically insulating material (27), wherein the first (24) and the second (26)
15 conductors are electrically connected to the control/power supply unit (40) and have respective first terminals (24a) inside the sheet (21), connected together; and
b) the control/power supply unit comprises:
20 - a power supply group (41) for the heating element (22), intended for connection to the electric mains,
- control means (45, 50) of the power supply for the heating element (22), such control means
25 including:
- a power supply cut-off group (45) for the heating element (22),
- a microprocessor (50), connected to the
30 heating element (22), to the power supply group (41) and to the cut-off group (45), set to detect possible anomalies in the power supply conditions of the heating element (22) and to act upon the cut-off group (45) interrupting the power supply of the heating element (22) when said anomalies take place;
35 characterised in that each anomaly detected is classified by the microprocessor (50) either as a

10. MAR. 2005 17:22

PCA +39 02 58301263

NR. 467 P. 6/16

IME012BWO

- 19 -

temporary anomaly or as a definitive anomaly, and wherein the interruption of the power supply of the heating element (22) is reversible in case of a temporary anomaly and irreversible in case of a definitive anomaly.

5

2. Heat blanket according to claim 1, wherein said anomalies include one or more of the following conditions:

- interruption of electric conduction in the heating element (22);
- short circuit in the heating element (22);
- overheating of the heating element (22);
- need or suitability of periodic maintenance.

10

15

3. Heat blanket according to claim 1, wherein a short-circuit in the heating element (22) and/or a need or suitability of periodical maintenance are classified as a definitive anomaly.

20

4. Heat blanket according to claim 3, wherein a decrease in impedance greater than a predetermined value, preferably 5%, is considered a short circuit.

25

5. Heat blanket according to claim 1, wherein overheating in the heating element (22) and/or an interruption in electric conduction in the heating element (22) and/or a need for or suitability of periodical maintenance are classified as temporary anomalies.

30

6. Heat blanket according to claim 1, wherein a temporary anomaly is reclassified as a definitive anomaly if it repeats a predetermined number of times.

7. Heat blanket according to claim 1, wherein the first and second conductors (24, 26) are coaxial, the first conductor (24) being wound in a spiral around a core

- 20 -

- (23), the second conductor (26) being wound in a spiral around the first conductor (24) with interposition of the first electrically insulating material (25), and wherein the first electrically insulating material (25) has a melting point of between 100 and 160 °C, preferably equal to about 120 °C.
- 5
8. Heat blanket according to claim 1, wherein the cut-off group (45) comprises, in series on the power supply of the conductors (24, 26), a first electronic operating switch (46), which activates or deactivates the electric conduction upon the command of the microprocessor (50) based upon the temperature of the heating element (22).
- 10
9. Heat blanket according to claim 8, wherein the electric resistance of the heating element (22) increases as the temperature increases and wherein the microprocessor (50) detects the temperature of the heating element (22) by a measurement of such an electric resistance.
- 15
- 20
10. Heat blanket according to claim 8, comprising an adjustable temperature setting group (51) of the heating element (22) connected to the microprocessor (50), and wherein the first electronic operating switch (46) activates or deactivates the electric conduction upon the command of the microprocessor (50) also based upon the setting of the adjustable temperature setting group (51) of the heating element (22).
- 25
11. Heat blanket according to claim 8, wherein the cut-off group comprises, in series on the power supply of the conductors (24, 26) and in series with the first electronic operating switch (46), a second electronic emergency switch (47).
- 30

- 21 -

12. Heat blanket according to claim 11, wherein the second electronic emergency switch (47) is such as to interrupt the circuit unless it is receiving a predetermined signal which is dependent upon an output signal from the microprocessor (50).
13. Heat blanket according to claim 11, wherein the second electronic emergency switch (47) is such as to interrupt the circuit in the case in which the resistance of the heating element (22) exceeds a predetermined threshold, independently of any command of the microprocessor (50).
14. Heat blanket according to claim 13, wherein the predetermined threshold is adjustable through the adjustable temperature setting group (51).
15. Heat blanket according to claim 1, comprising a signal indicator light (52), commanded by the microprocessor (50) according to specific and different cycles according to the classification of the anomaly detected.
16. Heat blanket according to claim 15, comprising a timer for the automatic interruption of the power supply of the heat blanket after a predetermined time, such an automatic interruption being indicated by a specific indication cycle of the signal indicator light (52).
17. Heat blanket according to claim 1, comprising an on-off indicator light (44), to indicate the electric power supply of the heat blanket.
18. Heat blanket according to claim 15, comprising an on-off indicator light (44), to indicate the electric power supply of the heat blanket, wherein the signal indicator light (52) and the on-off indicator light (44) are distinct and different from each other.

- 22 -

19. Heat blanket according to claim 1, wherein the
microprocessor (50) automatically and periodically
activates a self-diagnosis procedure, simulating its
own failure, checking the correct intervention of the
cut-off group (45) and finally either restoring its
operation in case of correct operation of the cut-off
group (45) or else indicating an anomaly in case of
irregular operation of the cut-off group (45).
20. Heat blanket according to claim 2, wherein the need
or suitability of programmed maintenance is
established by the microprocessor (50) based upon one
or more of the following parameters:
- total time that the blanket has been switched on;
 - total lifetime of the blanket;
 - total number of switching on and off cycles
undergone by the blanket;
 - number and type of anomalies detected.